


POLES



110 V
50-60 Hz

230 V
50-60 Hz

400 V
50-60 Hz

500 V
50-60 Hz

100-300 Hz
> 50 V

301-500 Hz
> 50 V

Std Pack

weight

Ampere

Poles

3pol. 4h 4h 4h 5pol. 3pol. 4h 6h 9h 5pol. 9h 3pol. 4h 6h 9h 5pol. 6h 6h 7h 3pol. 4h 7h 5pol. 7h 3pol. 10h 4pol. 10h 5pol. 10h 3pol. 2h 4pol. 2h 5pol. 2h

Qty g/ each



TYP 16 11

16	3		16 19				1	640
16	4		16 41	16 10	16 16		1	720
16	5		16 42	16 11			1	730



TYP 16 526

16	4		16 058	16 038	16 064		1	1150
16	5			16 526			1	1160



TYP 16 528

32	3		16 597				1	1270
32	4		16 931	16 596	16 825		1	1280
32	5			16 528			1	1290



TYP 16 603

63	3	16 093	16 956				1	2870
63	4		16 933	16 605	16 827		1	2900
63	5			16 603			1	3030


SURFACE MOUNTING SOCKET OUTLET Switched, Interlocked

IEC 60309, EN 60309, VDE 0623, BS-EN 60309

Protection degree IP 44

Enclosure and insert are made of high-quality plastic.

The hinged cover opens from the front which reduces the risk of dust and moisture getting inside the cover.




12 MB 3

AMPERE	16					
POLES	3	4	5			
a	90,0	90,0	90,0			
b	170,0	170,0	170,0			
c	77,0	77,0	77,0			
d	137,5	137,5	137,5			
e	108,0	114,0	121,0			
f	188,5	188,5	190,0			
g	6,0	6,0	6,0			
h Ø	5,5	5,5	5,5			
i	M 20	M 20	M 20			
k	M 20/25	M 20/25	M 20/25			

Surface-Mounting Socket Outlet

- switched
- in 0-position lockable
- with mechanical double interlocking
- splashproof IP 44




12 MB 24

AMPERE	16				
POLES	4	5			
a	118,0	118,0			
b	225,0	225,0			
c	101,0	101,0			
d	208,0	208,0			
e	126,0	134,0			
f	242,0	242,0			
g Ø	6,5	6,5			
h	8,0	8,0			
i	2 x M 25	2 x M 25			
k	2 x M 25	2 x M 25			

Surface-Mounting Socket Outlet

- switched
- in 0-position lockable
- with mechanical double interlocking
- splashproof IP 44




12 MB 24

AMPERE	32					
POLES	3	4	5			
a	118,0	118,0	118,0			
b	225,0	225,0	225,0			
c	101,0	101,0	101,0			
d	208,0	208,0	208,0			
e	137,0	137,0	144,0			
f	251,0	251,0	251,0			
g Ø	6,5	6,5	6,5			
h	8,0	8,0	8,0			
i	2 x M 25	2 x M 25	2 x M 25			
k	2 x M 25	2 x M 25	2 x M 25			

Surface-Mounting Socket Outlet

- switched
- in 0-position lockable
- with mechanical double interlocking
- splashproof IP 44



12 MB 30

AMPERE	63					
POLES	3	4	5			
a	160,0	160,0	160,0			
b	260,0	260,0	260,0			
c	140,0	140,0	140,0			
d	240,0	240,0	240,0			
e	184,0	184,0	184,0			
f	302,0	302,0	302,0			
g Ø	8,1	8,1	8,1			
h	10,0	10,0	10,0			
i	M 40	M 40	M 40			
k	M 32/40	M 32/40	M 32/40			

Surface-Mounting Socket Outlet

- switched
- in 0-position lockable
- with mechanical double interlocking
- Kontex Plus
- box terminals
- splashproof IP 44